MULTI-ZONE SOLUTIONS

Single zone features, benefits, and performance, available for multi-zone applications.

Matching one outdoor unit with a variety of multiple indoor units provides contractors unprecedented application flexibility.

ENERGY STAR

Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet **ENERGY STAR® Criteria.**
Ask your contractor for details or visit www.energystar.gov.

ALTITUDE™

ENDURE™

AHRI CERTIFIED® www.ahridirectory.org

SmartHQ™ HOME

SmartHQ™ SERVICE

GE APPLIANCES *a Haier company*

AIR&WATER SOLUTIONS

MULTI-ZONE SOLUTIONS

OPERATING RANGE (°F):



Cooling below 23°F requires wind baffle.

EASIER TO: DO THE JOB

R454B REFRIGERANT
A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.

OVER-THE-AIR UPDATES
A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.

EASIER TO: CLOSE THE SALE

DC INVERTER TECHNOLOGY
Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.

BLUE FIN
A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.

AUTO START
Auto restart automatically restarts the system after a power outage for seamless operation.

TEN-YEAR LIMITED WARRANTY
Double the standard five-year limited warranty simply by registering the unit, giving your homeowners additional peace of mind. See warranty documentation for complete details.

OPERATING RANGE (°F):

Cooling below 23°F requires wind baffle.

EASIER TO: DO THE JOB

R454B REFRIGERANT
A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.

OVER-THE-AIR UPDATES
A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.

EASIER TO: CLOSE THE SALE

DC INVERTER TECHNOLOGY
Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.

BLUE FIN
A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.

AUTO START
Auto restart automatically restarts the system after a power outage for seamless operation.

BASEPAN HEATER
A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.

-22°F HEATING
Reliable low ambient heating down to -22°F ensures comfort and efficiency even in extreme conditions.

MULTI-ZONE

OUTDOOR UNIT SPECIFICATIONS

ALTITUDE™

		2 Zones	3 Zones	4 Zones
				
		2G18AD2BEA	3G24AD2BEA	4G36AD2BEA
Cooling Non-Ducted	Rated Capacity Btu/hr	18,000	24,000	35,000
	Capacity Range Btu/hr	4,000-19,000	4,000-25,000	6,500-36,000
	SEER2	22.5	24.0	20.0
	EER2	12.0	12.0	10.0
Cooling Ducted	Rated Capacity Btu/hr	17,000	24,000	33,400
	Capacity Range Btu/hr	4,000-18,000	4,000-25,000	6,500-34,000
	SEER2	18.8	17.2	16.5
	EER2	10.8	10.5	8.8
Heating Non-Ducted	Rated Heating Capacity 47°F Btu/hr	21,000	27,000	36,000
	Capacity Range Btu/hr	4,000-22,000	4,000-28,000	6,500-37,000
	HSPF2 (IV)	10.5	10.2	10.0
	Rated Heating Capacity 5°F Btu/hr	16,600	17,600	23,000
	Heating Capacity at 5°F / Capacity at 47°F	79.0%	65.2%	63.9%
	COP @ 5°F / COP @ 47°F	1.8 / 3.6	1.8 / 3.9	1.8 / 3.2
Heating Ducted	Rated Heating Capacity 47°F Btu/hr	19,000	25,000	35,600
	Capacity Range Btu/hr	4,000-20,000	4,000-26,000	6,500-36,000
	HSPF2 (IV)	9.5	9.5	9.3
	Rated Heating Capacity 5°F Btu/hr	15,000	17,000	21,000
	Heating Capacity at 5F / Capacity at 47F	77.0%	67.0%	60.0%
	COP @ 5°F / COP @ 47°F	1.8 / 3.7	1.8 / 3.6	1.8 / 3.3
Operating Range	Cooling °F (°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)
	Heating °F (°C)	-4~75°F (-20~24°C)	-4~75°F (-20~24°C)	-4~75°F (-20~24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1
	Wire Size Between IDU and ODU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU
	Maximum Fuse Size A	25	25	30
	Minimum Circuit Amp A	16	18	22
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Fan Speed RPM	200~700	200~700	250~780
	Outdoor Noise Level dB	52	53	58
	Dimension: Height in (mm)	27 9/16 (700)	27 9/16 (700)	30 1/8 (765)
	Dimension: Width in (mm)	36 (915)	36 (915)	37 3/16 (945)
	Dimension: Depth in (mm)	14 1/2 (368)	14 1/2 (368)	15 13/16 (402)
	Weight (Net/Ship)- lbs (kg)	112/130 (51/59)	119/137 (54/62)	134/152 (61/69)
	Basepan Heater	No	No	No
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4 1/4	1/4 1/4 1/4	1/4 1/4 1/4 1/4
	Suction O.D. in	3/8 3/8	3/8 3/8 3/8	3/8 3/8 3/8 1/2
	Factory Charge Oz	53	60	81
	Maximum Line Length Ft / m	98/30	197/60	230/70
	Maximum Height Ft / m	50/15	50/15	50/15
	Minimum Line Length for Each Individual Indoor Unit Ft / m	10/3	10/3	10/3
	Maximum Line Length for Each Individual Indoor Unit Ft / m	65/20	82/25	82/25
	Maximum Line Length without Additional Charge Ft / m	66/20	100/30	131/40

MULTI-ZONE

OUTDOOR UNIT SPECIFICATIONS

ENDURE™

		2 Zones	3 Zones	4 Zones	5 Zones
		2G20ED2BEA	3G24ED2BEA	4G36ED2BEA	5G42ED2BEA
Cooling Non-Ducted	Rated Capacity Btu/hr	18,000	24,000	36,000	42,000
	Capacity Range Btu/hr	4,000-19,000	4,000-25,000	6,500-36,500	6,500-42,500
	SEER2	20.6	23.0	20.5	20.5
	EER2	12.3	12.2	11.0	10.5
Cooling Ducted	Rated Capacity Btu/hr	17,000	24,000	35,000	42,000
	Capacity Range Btu/hr	4,000-18,000	4,000-25,000	6,500-35,500	6,500-42,500
	SEER2	17.6	17.2	17.4	17.4
	EER2	10.8	10.5	10.2	10.2
Heating Non-Ducted	Rated Heating Capacity 47°F Btu/hr	22,000	25,000	36,000	42,500
	Capacity Range Btu/hr	4,000-23,000	4,000-26,000	6,500-37,000	6,500-43,500
	HSPF2 (IV)	10.5	10.5	10.0	9.5
	Rated Heating Capacity 5°F Btu/hr	20,000	22,800	34,000	35,000
	Heating Capacity at 5F / Capacity at 47F	91%	91%	94%	81%
	COP @ 5°F / COP @ 47°F	1.8 / 3.7	1.8 / 3.6	1.8 / 3.7	1.8 / 3.6
Heating Ducted	Rated Heating Capacity 47°F Btu/hr	22,000	26,000	35,000	42,500
	Capacity Range Btu/hr	4,000-23,000	4,000-27,000	6,500-36,000	6,500-43,500
	HSPF2 (IV)	10.5	10.0	10.0	9.5
	Rated Heating Capacity 5°F Btu/hr	20,000	22,000	30,000	35,000
	Heating Capacity at 5F / Capacity at 47F	90%	85%	84%	83%
	COP @ 5°F / COP @ 47°F	1.8 / 3.6	1.8 / 3.5	1.8 / 3.9	1.8 / 3.5
Operating Range	Cooling °F (°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)
	Heating °F (°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
	Wire Size Between IDU and ODU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU
	Maximum Fuse Size A	30	30	40	40
	Minimum Circuit Amp A	20	21	35	36
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Fan Speed RPM	250~780	250~780	250~650	250~650
	Outdoor Noise Level dB	57	57	60	62
	Dimension: Height in (mm)	30 1/8 (765)	30 1/8 (765)	33 1/16 (840)	33 1/16 (840)
	Dimension: Width in (mm)	37 3/16 (945)	37 3/16 (945)	41 3/4 (1060)	41 3/4 (1060)
	Dimension: Depth in (mm)	15 13/16 (402)	15 13/16 (402)	15 13/16 (402)	15 13/16 (402)
	Weight (Net/Ship) - lbs (kg)	130/148 (59/67)	132/150 (60/68)	198/243 (90/110)	201/245 (91/111)
	Basepan Heater	Yes	Yes	Yes	Yes
Refrigerant Lines	Refrigerant	R454B	R454B	R454B	R454B
	Connections	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4 1/4	1/4 1/4 1/4	1/4 1/4 1/4 1/4	1/4 1/4 1/4 1/4 1/4
	Suction O.D. in	3/8 3/8	3/8 3/8 3/8	3/8 3/8 3/8 1/2	3/8 3/8 3/8 1/2 1/2
	Factory Charge Oz	60	71	113	123
	Maximum Line Length Ft / m	164/50	197/60	230/70	262/80
	Maximum Height Ft / m	50/15	50/15	50/15	50/15
	Minimum Line Length for Each Individual Indoor Unit Ft / m	10/3	10/3	10/3	10/3
	Maximum Line Length for Each Individual Indoor Unit Ft / m	82/25	82/25	82/25	82/25
	Maximum Line Length Without Additional Charge Ft / m	66/20	100/30	131/40	164/50

MULTI-ZONE

OUTDOOR/INDOOR MATCHING TABLE

			OUTDOOR UNITS						
			ALTITUDE™			ENDURE™			
			2G18AD2BEA	3G24AD2BEA	4G36AD2BEA	2G20ED2BEA	3G24ED2BEA	4G36ED2BEA	5G42ED2BEA
	Standard Highwall	GS07WB2BEA	✓	✓	✓	✓	✓	✓	✓
		GS09WB2BEA	✓	✓	✓	✓	✓	✓	✓
		GS12WB2BEA	✓	✓	✓	✓	✓	✓	✓
		GS15WB2BEA	✓	✓	✓	✓	✓	✓	✓
		GS18WB2BEA		✓	✓		✓	✓	✓
		GS24WB2BEA		✓	✓			✓	✓
	Premium Highwall	GS09WP2BEA	✓	✓	✓	✓	✓	✓	✓
		GS12WP2BEA	✓	✓	✓	✓	✓	✓	✓
		GS18WP2BEA		✓	✓		✓	✓	✓
		GS24WP2BEA		✓	✓			✓	✓
	Compact Cassette	US09CB2BEA	✓	✓	✓	✓	✓	✓	✓
		US12CB2BEA	✓	✓	✓	✓	✓	✓	✓
		US18CB2BEA		✓	✓		✓	✓	✓
	Large Cassette	US24LB2BEA		✓	✓			✓	✓
	Floor Console	US09FB2BEA	✓	✓	✓	✓	✓	✓	✓
		US12FB2BEA	✓	✓	✓	✓	✓	✓	✓
		US18FB2BEA		✓	✓		✓	✓	✓
	Mid-Static Ducted	US09MB2BEA	✓	✓	✓	✓	✓	✓	✓
		US12MB2BEA	✓	✓	✓	✓	✓	✓	✓
		US18MB2BEA		✓	✓		✓	✓	✓
		US24MB2BEA		✓	✓			✓	✓

MULTI-ZONE

INDOOR UNIT SPECIFICATIONS

STANDARD HIGHWALL

EASIER TO: DO THE JOB

EXTENDED KICKSTAND
The built-in bracket provides extra room for easier installation and service.

MOUNTING TEMPLATE/PLATE
A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.

2-WAY PIPING DRAIN
Flexible right or left side condensation drain options simplify installation (right side only with RDS installed).

EASY-ACCESS PCB
The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.

EASIER TO: CLOSE THE SALE

AUTO LOUVER
Designed to oscillate up and down automatically for even air distribution.

WARM START
Ensures the fan does not blow cold air during heating mode startup.

TURBO MODE
Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

INDOOR AIR FILTER
The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

	GS07WB2BEA	GS09WB2BEA	GS12WB2BEA	GS15WB2BEA	GS18WB2BEA	GS24WB2BEA
Rated Capacity Btu/hr	7,000	9,000	12,000	15,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1250/1050/950/850/750	1250/1050/950/850/750	1250/1100/1000/900/750	1400/1350/1100/850/610	1250/1150/1050/950/800	1300/1200/1050/900/750
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1020/895/770/700	1200/1020/895/770/700	1200/1020/920/820/700	1400/1350/1200/1050/610	1250/1150/1025/900/750	1300/1200/1050/900/750
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	360/290/260/230/210	360/290/260/230/210	360/300/272/240/210	410/370/280/210/170	570/520/480/420/330	800/730/630/535/440
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	350/290/250/220/200	350/290/250/220/200	350/290/260/230/200	420/390/350/310/180	570/520/450/380/310	800/730/630/535/440
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/38/35/32/27	44/38/35/32/27	44/39/36/33/27	46/45/40/33/26	50/46/44/40/35	54/50/47/44/38
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/36/32/28/26	42/36/32/28/26	42/36/32/29/26	44/43/40/37/23	48/46/41/38/33	54/50/47/44/38
Auto Up-Down Louver	Yes	Yes	Yes	Yes	Yes	Yes
Auto Left-Right Louver	No	No	No	No	No	No
Dimension: H x W x D in (mm)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	12 1/4 x 36 1/8 x 8 3/8 (312 x 918 x 213)	12 7/8 x 39 3/8 x 8 3/4 (327 x 999 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)
Weight (Net/Ship)- lbs (kg)	21.62/26.7 (9.8/12.1)	21.84/26.92 (9.9/12.2)	21.84/26.92 (9.9/12.2)	24.49/30.45 (11.1/13.8)	27.8/34.64 (12.6/15.7)	34.86/43.03 (15.8/19.5)
Liquid O.D. in	1/4	1/4	1/4	1/4	1/4	1/4
Suction O.D. in	3/8	3/8	3/8	3/8	1/2	1/2
Drain Pipe Size O.D in	5/8	5/8	5/8	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE

INDOOR UNIT SPECIFICATIONS

PREMIUM HIGHWALL

EASIER TO: DO THE JOB

EXTENDED KICKSTAND
The built-in bracket provides extra room for easier installation and service.

MOUNTING TEMPLATE/PLATE
A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.

2-WAY PIPING DRAIN
Flexible right or left side condensation drain options simplify installation (right side only with RDS installed).

EASY-ACCESS PCB
The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.

EASIER TO: CLOSE THE SALE

WARM START
Ensures the fan does not blow cold air during heating mode startup.

TURBO MODE
Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

INDOOR AIR FILTER
The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

3-D AIRFLOW
Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.

SMART SENSOR
Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.

FOLLOW & SURROUND
Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

	GS09WP2BEA	GS12WP2BEA	GS18WP2BEA	GS24WP2BEA
Rated Capacity Btu/hr	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1200/1100/875/650/610	1300/1250/1050/850/610	1300/1250/1050/850/800	1300/1200/1050/900/750
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1100/900/700/610	1300/1250/1150/1050/610	1300/1250/1025/800/750	1300/1200/1050/900/750
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	395/355/310/260/170	410/370/280/210/170	580/530/480/400/350	800/730/630/535/440
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	395/355/290/220/170	420/390/350/310/180	580/530/450/350/320	800/730/630/535/440
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/42/36/32/27	46/44/38/32/25	51/50/44/37/25	54/50/47/44/38
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/41/37/32/29	43/42/39/36/25	49/47/40/35/26	54/50/47/44/38
Auto Up-Down Louver	Yes	Yes	Yes	Yes
Auto Left-Right Louver	Yes	Yes	Yes	Yes
Dimension: H x W x D in (mm)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)
Weight (Net/Ship)- lbs (kg)	24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)	34.86/43.03 (15.8/19.5)
Liquid O.D. in	1/4	1/4	1/4	1/4
Suction O.D. in	3/8	3/8	1/2	1/2
Drain Pipe Size O.D in	5/8	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE

INDOOR UNIT SPECIFICATIONS

CASSETTE

EASIER TO: DO THE JOB

COMPACT DESIGN
Fits 2' x 2' drop ceiling for easy installation.

CONDENSATE PUMP
Factory-installed condensate pump.

FRESH AIR KNOCKOUT
Unit designed with a 4" round fresh air knockout.

EASIER TO: CLOSE THE SALE

WARM START
Ensures the fan does not blow cold air during heating mode startup.

TURBO MODE
Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

INDEPENDENT LOUVER CONTROL
The four cassette louvers can be set to the same, or different positions, to control airflow direction.

	US09CB2BEA	US12CB2BEA	US18CB2BEA	US24LB2BEA
Panel Model	GACCP01GA	GACCP01GA	GACCP01GA	GALCP01GA
Rated Capacity Btu/hr	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	830/760/690/620/560	830/760/690/620/560	850/800/760/680/590	620/580/540/430/360
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	830/760/690/620/560	830/760/690/620/560	850/800/760/680/590	620/580/540/430/360
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	458/425/387/345/302	1033/873/858/640/400
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	479/441/387/345/302	1033/873/858/640/400
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32	46/44/41/38/35
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32	46/44/42/39/36
Chassis Dimension: HxWxD in (mm)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	9 3/4 x 33 x 33 (248 x 840 x 840)
Panel Dimension: HxWxD in (mm)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	1 15/16 x 37 3/8 x 37 3/8 (50 x 950 x 950)
Weight (Net/Ship)- lbs (kg)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	56.22/85.32 (25.5/38.7)
Liquid Pipe O.D. (in)	1/4	1/4	1/4	3/8
Suction Pipe O.D. (in)	3/8	3/8	1/2	5/8
Drainpipe Size O.D. (in)	1*	1*	1*	1*
Condensate Pump Built-In	Yes	Yes	Yes	Yes
Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
WiFi**	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)	Yes (UALS01A, sold seperately)

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE

INDOOR UNIT SPECIFICATIONS

CONSOLE

EASIER TO: DO THE JOB

AIRFLOW DIRECTION CONTROL
Allows the homeowner to select preferred airflow direction - the top and bottom or top only.

INSTALLATION FLEXIBILITY
Unit can be placed on the floor or installed low on the wall.

EASIER TO: CLOSE THE SALE

WARM START
Ensures the fan does not blow cold air during heating mode startup.

TURBO MODE
Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

ROOM TEMPERATURE DISPLAY
Easy-to-read dual seven segment display on the front of the panel.

	US09FB2BEA	US12FB2BEA	US18FB2BEA
Rated Capacity Btu/hr	9,000	12,000	18,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	700/560/480/410/360	800/590/510/440/390	850/710/690/560/510
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	700/560/480/410/360	800/590/510/440/390	850/710/690/560/510
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	290/218/205/176/147	314/226/210/195/175	345/341/271/218/210
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	312/206/205/176/147	311/223/200/195/175	345/300/280/218/210
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/40/37/32/24	47/41/37/33/25	49/44/43/40/37
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/37/32/27/20	47/40/37/33/25	49/43/43/37/37
Dimension: HxWxD in (mm)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)
Weight (Net/Ship)- lbs (kg)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)
Liquid Pipe O.D. (in)	1/4	1/4	1/4
Suction Pipe O.D. (in)	3/8	3/8	1/2
Drainpipe Size O.D. in	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE

INDOOR UNIT SPECIFICATIONS

MID-STATIC DUCTED

AUXILIARY HEATER COMPATIBLE
Compatible with many third-party auxiliary heaters.

FRESH AIR KNOCKOUT
Unit designed with a 4" round fresh air knockout.

EASIER TO: DO THE JOB

COMPACT DESIGN
Less than 10" height saves ceiling space.

CONDENSATE PUMP
Factory-installed condensate pump.

0.6" EXTERNAL STATIC
Designed for static pressure up to 0.6" w.g.

EASIER TO: CLOSE THE SALE

WARM START
Ensures the fan does not blow cold air during heating mode startup.

TURBO MODE
Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

OPTIONAL ACCESSORIES
MERV filter box and supply plenums available (sold separately) for easy installation.

	US07MB2BEA	US09MB2BEA	US12MB2BEA	US18MB2BEA	US24MB2BEA
Rated Cooling Capacity Btu/hr	7,000	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	830/780/700/640/560	880/800/720/640/560	950/870/780/680/600	880/820/760/700/640	1070/1030/880/790/740
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	830/780/700/640/560	880/800/720/640/560	950/870/780/680/600	880/820/760/700/640	1070/1030/880/790/740
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	335/272/190/150/141	353/286/200/150/141	409/350/308/158/148	620/517/332/214/203	927/844/667/564/482
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	335/272/190/150/141	358/292/208/155/145	412/355/311/163/152	627/523/337/217/205	927/844/667/564/482
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/39/37/35/32	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	47/46/41/38/37
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/39/37/35/32	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	46/45/40/38/36
Dimension: HxWxD in (mm)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)
Weight (Net/Ship)- lbs (kg)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	87.74/123.46 (39.8/56)	87.74/123.46 (39.8/56)
Max. External Static Pressure in.W.G (Pa)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)
Liquid Pipe O.D. (in)	1/4	1/4	1/4	1/4	3/8
Suction Pipe O.D. (in)	3/8	3/8	3/8	1/2	5/8
Drainpipe Size	1*	1*	1*	1*	1*
Condensate Pump Built-In	Yes	Yes	Yes	Yes	Yes
Max. Drain-Lift Height in(mm)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)
WiFi**	Built-in	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes	Yes	Yes

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE CAPACITY COMBINATION MATRIX

2G20ED2B**
2G18AD2B**

- No adapters required/shipped

	Combinations	
	Port B	Port A
	Port Size: 1/4" x 3/8"	Port Size: 1/4" x 3/8"
Two Zone	7K	7K
	9K	7K
	9K	9K
	12K	7K
	12K	9K
	12K	12K
	15K	7K
	15K	9K

3G24ED2B** (Ships with adapter D)
3G24AD2B**(Ships with adapter D)

- No adapters required for Ports B, A

	Combinations			
	Port C		Port B	Port A
	Port Size: 1/4" x 3/8"	Required Adapter	Port Size: 1/4" x 3/8"	Port Size: 1/4" x 3/8"
Two Zone	7K	-	7K	-
	9K	-	7K	-
	9K	-	9K	-
	12K	-	7K	-
	12K	-	9K	-
	12K	-	12K	-
	15K	-	7K	-
	15K	-	9K	-
	15K	-	12K	-
	15K	-	15K	-
	18K	D	7K	-
	18K	D	9K	-
	18K	D	12K	-
Three Zone	7K	-	7K	7K
	9K	-	7K	7K
	9K	-	9K	7K
	9K	-	9K	9K
	12K	-	7K	7K
	12K	-	9K	7K
	12K	-	9K	9K
	12K	-	12K	7K
	12K	-	12K	9K
	15K	-	7K	7K
	15K	-	9K	7K
	15K	-	9K	9K
	18K	D	7K	7K

4G36ED2B** (Ships with adapters D and E)
4G36AD2B** (Ships with adapters D and E)

- No adapters required for Ports B, A

	Combinations					
	Port D		Port C		Port B	Port A
	Port Size: 1/4" x 1/2"	Required Adapter	Port Size: 1/4" x 3/8"	Required Adapter	Port Size: 1/4" x 3/8"	Port Size: 1/4" x 3/8"
Two Zone	18K	-	9K	-	-	-
	18K	-	12K	-	-	-
	18K	-	15K	-	-	-
	18K	-	18K	D	-	-
	18K	-	24K	A, B D	-	-
	24K	A, C -	7K	-	-	-
	24K	A, C -	9K	-	-	-
	24K	A, C -	12K	-	-	-
	24K	A, C -	15K	-	-	-
	24K	A, C -	24K	A, B D	-	-
Three Zone	-	-	9K	-	9K	9K
	-	-	12K	-	9K	7K
	-	-	12K	-	9K	9K
	-	-	12K	-	12K	7K
	-	-	12K	-	12K	9K
	-	-	12K	-	12K	12K
	-	-	15K	-	7K	7K
	-	-	15K	-	9K	7K
	-	-	15K	-	12K	7K
	-	-	15K	-	15K	7K
	-	-	15K	-	12K	7K
	-	-	15K	-	9K	9K
	-	-	15K	-	12K	9K
	-	-	15K	-	15K	9K
	-	-	15K	-	12K	12K
	-	-	15K	-	15K	12K
	-	-	15K	-	15K	15K
	18K	-	7K	-	7K	-
	18K	-	9K	-	7K	-
	18K	-	9K	-	9K	-
	18K	-	12K	-	7K	-
	18K	-	12K	-	9K	-
	18K	-	12K	-	12K	-
	18K	-	15K	-	7K	-
	18K	-	15K	-	9K	-
	18K	-	15K	-	12K	-
	18K	-	15K	-	15K	-
	18K	-	18K	D	7K	-
	18K	-	18K	D	9K	-
	18K	-	18K	D	12K	-
	24K	A, C -	7K	-	7K	-
	24K	A, C -	9K	-	7K	-
	24K	A, C -	9K	-	9K	-
	24K	A, C -	12K	-	7K	-
	24K	A, C -	12K	-	9K	-
	24K	A, C -	12K	-	12K	-
	24K	A, C -	15K	-	7K	-
	24K	A, C -	15K	-	9K	-
Four Zone	7K	E	7K	-	7K	7K
	9K	E	7K	-	7K	7K
	9K	E	9K	-	7K	7K
	9K	E	9K	-	9K	7K
	9K	E	9K	-	9K	9K
	12K	E	7K	-	7K	7K
	12K	E	9K	-	7K	7K
	12K	E	9K	-	9K	7K
	12K	E	9K	-	9K	9K
	12K	E	12K	-	7K	7K
	12K	E	12K	-	9K	7K
	12K	E	12K	-	9K	9K
	12K	E	12K	-	12K	7K
	12K	E	12K	-	12K	9K
	12K	E	12K	-	12K	12K
	15K	E	7K	-	7K	7K
	15K	E	9K	-	7K	7K
	15K	E	9K	-	9K	7K
	15K	E	9K	-	9K	9K
	15K	E	12K	-	7K	7K
	15K	E	12K	-	9K	7K
	15K	E	12K	-	9K	9K
	15K	E	12K	-	12K	7K
	15K	E	12K	-	12K	9K
	15K	E	15K	-	7K	7K
	15K	E	15K	-	9K	7K
	15K	E	15K	-	9K	9K
	18K	-	7K	-	7K	7K
	18K	-	9K	-	7K	7K
	18K	-	9K	-	9K	7K
	18K	-	9K	-	9K	9K
	18K	-	12K	-	7K	7K
	18K	-	12K	-	9K	7K
	18K	-	12K	-	9K	9K
	18K	-	15K	-	7K	7K
	24K	A, C -	7K	-	7K	7K
	24K	A, C -	9K	-	7K	7K

Lineset Adapters		Part #
A	1/4" to 3/8" (Liquid line for ports C & D)	WJ01X35713
B	3/8" to 5/8" (Vapor line for port C)	WJ01X35714
C	1/2" to 5/8" (Vapor line for port D)	WJ01X35715
D	3/8"to 1/2" (Vapor line for port C)	WJ01X35716
E	1/2" to 3/8" (Vapor line for port C or D)	WJ01X35717

These 24K models require 3/8" liquid and 5/8" vapor linesets US24LB2BE**, US24MB2BE**

These 24K models require 1/4" liquid and 1/2" vapor linesets GS24WB2B**, GS24WP2B**

All 18K models require 1/4" liquid and 1/2" vapor linesets.
All 7K, 9K, 12K and 15K models require 1/4" liquid and 3/8" vapor linesets.

MULTI-ZONE CAPACITY COMBINATION MATRIX

5G42ED2B (Ships with two (2) adapter E)**

- No adapters required for Ports B, A

	Combinations							
	Port E		Port D		Port C		Port B	Port A
	Port Size: 1/4" x 1/2"	Required Adapter*	Port Size: 1/4" x 1/2"	Required Adapter*	Port Size: 1/4" x 3/8"	Required Adapter*	Port Size: 1/4" x 3/8"	Port Size: 1/4" x 3/8"
Two Zone	18K	-	-	-	9K	-	-	-
	18K	-	-	-	12K	-	-	-
	18K	-	-	-	15K	-	-	-
	18K	-	18K	-	-	-	-	-
	24K	A, C -	-	-	7K	-	-	-
	24K	A, C -	-	-	9K	-	-	-
	24K	A, C -	-	-=	12K	-	-	-
	24K	A, C -	-	-	15K	-	-	-
	24K	A, C -	18K	-	-	-	-	-
	24K	A, C -	24K	A, C -	-	-	-	-
Three Zone	-	-	-	-	9K	-	9K	9K
	-	-	-	-	12K	-	9K	9K
	-	-	-	-	12K	-	9K	7K
	-	-	-	-	12K	-	12K	7K
	-	-	-	-	12K	-	12K	9K
	-	-	-	-	12K	-	12K	12K
	-	-	-	-	15K	-	7K	7K
	-	-	-	-	15K	-	9K	7K
	-	-	-	-	15K	-	9K	9K
	-	-	-	-	15K	-	12K	7K
	-	-	-	-	15K	-	12K	9K
	-	-	-	-	15K	-	12K	12K
	-	-	-	-	15K	-	15K	7K
	-	-	-	-	15K	-	15K	9K
	-	-	-	-	15K	-	15K	12K
	-	-	-	-	15K	-	15K	15K
	18K	-	-	-	7K	-	7K	-
	18K	-	-	-	9K	-	7K	-
	18K	-	-	-	9K	-	9K	-
	18K	-	-	-	12K	-	7K	-
	18K	-	-	-	12K	-	9K	-
	18K	-	-	-	12K	-	12K	-
	18K	-	-	-	15K	-	7K	-
	18K	-	-	-	15K	-	9K	-
	18K	-	-	-	15K	-	12K	-
	18K	-	-	-	15K	-	15K	
	18K	-	18K	-	7K	-	-	-
	18K	-	18K	-	9K	-	-	-
	18K	-	18K	-	12K	-	-	-
	18K	-	18K	-	15K	-	-	-
	18K	-	18K	-	18K	D	-	-
	24K	A, C -	-	-	7K	-	7K	-
	24K	A, C -	-	-	9K	-	7K	-
	24K	A, C -	-	-	9K	-	9K	-
	24K	A, C -	-	-	12K	-	7K	-
	24K	A, C -	-	-	12K	-	9K	-
	24K	A, C -	-	-	12K	-	12K	-
	24K	A, C -	-	-	15K	-	7K	-
	24K	A, C -	-	-	15K	-	9K	-
	24K	A, C -	-	-	15K	-	12K	-
	24K	A, C -	18K	-	7K	-	-	-
	24K	A, C -	18K	-	9K	-	-	-
	24K	A, C -	18K	-	12K	-	-	-
	24K	A, C -	18K	-	15K	-	-	-
Four Zone	7K	E	-	-	7K	-	7K	7K
	9K	E	-	-	7K	-	7K	7K
	9K	E	-	-	9K	-	7K	7K
	9K	E	-	-	9K	-	9K	7K
	9K	E	-	-	9K	-	9K	9K
	12K	E	-	-	7K	-	7K	7K
	12K	E	-	-	9K	-	7K	7K
	12K	E	-	-	9K	-	9K	7K
	12K	E	-	-	9K	-	9K	9K
	12K	E	-	-	12K	-	7K	7K
	12K	E	-	-	12K	-	9K	7K
	12K	E	-	-	12K	-	9K	9K
	12K	E	-	-	12K	-	12K	7K
	12K	E	-	-	12K	-	12K	9K
	12K	E	-	-	12K	-	12K	12K
	15K	E	-	-	7K	-	7K	7K
	15K	E	-	-	9K	-	7K	7K
	15K	E	-	-	9K	-	9K	7K
	15K	E	-	-	9K	-	9K	9K
	15K	E	-	-	12K	-	7K	7K
	15K	E	-	-	12K	-	9K	7K
	15K	E	-	-	12K	-	9K	9K
	15K	E	-	-	12K	-	12K	7K
	15K	E	-	-	12K	-	12K	9K
	15K	E	-	-	12K	-	12K	12K
	15K	E	-	-	15K	-	7K	7K
	15K	E	-	-	15K	-	9K	7K

	Combinations							
	Port E		Port D		Port C		Port B	Port A
	Port Size: 1/4" x 1/2"	Required Adapter*	Port Size: 1/4" x 1/2"	Required Adapter*	Port Size: 1/4" x 3/8"	Required Adapter*	Port Size: 1/4" x 3/8"	Port Size: 1/4" x 3/8"
Four Zone (Cont'd)	15K	E	-	-	15K	-	9K	9K
	15K	E	-	-	15K	-	12K	9K
	15K	E	-	-	15K	-	12K	12K
	15K	E	-	-	15K	-	15K	12K
	18K	-	-	-	7K	-	7K	7K
	18K	-	-	-	9K	-	7K	7K
	18K	-	-	-	9K	-	9K	7K
	18K	-	-	-	9K	-	9K	9K
	18K	-	-	-	12K	-	7K	7K
	18K	-	-	-	12K	-	9K	7K
	18K	-	-	-	12K	-	9K	9K
	18K	-	-	-	12K	-	12K	7K
	18K	-	-	-	12K	-	12K	9K
	18K	-	-	-	12K	-	12K	12K
	18K	-	-	-	15K	-	7K	7K
	18K	-	-	-	15K	-	9K	7K
	18K	-	-	-	15K	-	9K	9K
	18K	-	-	-	15K	-	12K	7K
	18K	-	-	-	15K	-	12K	9K
	18K	-	-	-	15K	-	12K	12K
	18K	-	18K	-	7K	-	7K	-
	18K	-	18K	-	9K	-	7K	-
	18K	-	18K	-	9K	-	9K	-
	18K	-	18K	-	12K	-	7K	-
	18K	-	18K	-	12K	-	9K	-
	24K	A, C -	-	-	7K	-	7K	7K
	24K	A, C -	-	-	9K	-	7K	7K
	24K	A, C -	-	-	9K	-	9K	7K
	24K	A, C -	-	-	9K	-	9K	9K
	24K	A, C -	-	-	12K	-	7K	7K
	24K	A, C -	-	-	12K	-	9K	7K
	24K	A, C -	-	-	12K	-	12K	7K
	24K	A, C -	-	-	12K	-	9K	9K
	24K	A, C -	-	-	15K	-	7K	7K
	24K	A, C -	-	-	15K	-	9K	7K
	24K	A, C -	18K	-	7K	-	7K	-
Five Zone	7K	E	7K	E	7K	-	7K	7K
	9K	E	7K	E	7K	-	7K	7K
	9K	E	9K	E	7K	-	7K	7K
	9K	E	9K	E	9K	-	7K	7K
	9K	E	9K	E	9K	-	9K	7K
	9K	E	9K	E	9K	-	9K	9K
	12K	E	7K	E	7K	-	7K	7K
	12K	E	9K	E	7K	-	7K	7K
	12K	E	9K	E	9K	-	7K	7K
	12K	E	9K	E	9K	-	9K	7K
	12K	E	9K	E	9K	-	9K	9K
	12K	E	12K	E	7K	-	7K	7K
	12K	E	12K	E	9K	-	7K	7K
	12K	E	12K	E	9K	-	9K	7K
	12K	E	12K	E	9K	-	9K	9K
	12K	E	12K	E	12K	-	7K	7K
	12K	E	12K	E	12K	-	9K	7K
	12K	E	12K	E	12K	-	9K	9K
	12K	E	12K	E	12K	-	12K	7K
	12K	E	12K	E	12K	-	12K	9K
	12K	E	12K	E	12K	-	12K	12K
	18K	-	7K	E	7K	-	7K	7K
	18K	-	9K	E	7K	-	7K	7K
	18K	-	9K	E	9K	-	7K	7K
	18K	-	9K	E	9K	-	9K	7K
	18K	-	9K	E	9K	-	9K	9K
	18K	-	12K	E	7K	-	7K	7K
	18K	-	12K	E	9K	-	7K	7K
	18K	-	12K	E	9K	-	9K	7K
	18K	-	12K	E	9K	-	9K	9K
	18K	-	12K	E	12K	-	7K	7K
	18K	-	12K	E	12K	-	9K	7K
	18K	-	12K	E	12K	-	9K	9K
	18K	-	15K	E	7K	-	7K	7K
	18K	-	15K	E	9K	-	7K	7K
	18K	-	15K	E	9K	-	9K	7K
	18K	-	15K	E	9K	-	9K	9K
	18K	-	15K	E	12K	-	7K	7K
	24K	A, C -	7K	E	7K	-	7K	7K
	24K	A, C -	9K	E	7K	-	7K	7K
	24K	A, C -	9K	E	9K	-	7K	7K
	24K	A, C -	9K	E	9K	-	9K	7K
	24K	A, C -	9K	E	9K	-	9K	9K
	24K	A, C -	12K	E	7K	-	7K	7K
	24K	A, C -	12K	E	9K	-	7K	7K

Lineset Adapters

		Part #
A	1/4" to 3/8" (Liquid line for ports C & D)	WJ01X35713
B	3/8" to 5/8" (Vapor line for port C)	WJ01X35714
C	1/2" to 5/8" (Vapor line for port D)	WJ01X35715
D	3/8"to 1/2" (Vapor line for port C)	WJ01X35716
E	1/2" to 3/8" (Vapor line for port C or D)	WJ01X35717

These 24K models require 3/8" liquid and 5/8" vapor linesets US24LB2BE**, US24MB2BE**

These 24K models require 1/4" liquid and 1/2" vapor linesets GS24WB2B**, GS24WP2B**

All 18K models require 1/4" liquid and 1/2" vapor linesets.
All 7K, 9K, 12K and 15K models require 1/4" liquid and 3/8" vapor linesets.

GE APPLIANCES a Haier company | AIR&WATER SOLUTIONS

©Copyright 2025 GE Appliances, a Haier Company. GE is a trademark of the General Electric Company. Manufactured under trademark license. GE Appliances has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.

Pub No. 25-GMZ01
Rev. 07-30-25

www.GEAppliancesAirAndWater.com